

SERVICE MAPPINGS

-----

This memo describes the relationship between the Internet Protocol (IP) [1] Type of Service and the service parameters of specific networks.

The IP Type of Service has the following fields:

Bits 0-2: Precedence.  
Bit 3: 0 = Normal Delay, 1 = Low Delay.  
Bits 4: 0 = Normal Throughput, 1 = High Throughput.  
Bits 5: 0 = Normal Reliability, 1 = High Reliability.  
Bit 6-7: Reserved for Future Use.

0	1	2	3	4	5	6	7
PRECEDENCE			D	T	R	0	0

111 - Network Control  
110 - Internetwork Control  
101 - CRITIC/ECP  
100 - Flash Override  
011 - Flash  
010 - Immediate  
001 - Priority  
000 - Routine

The individual networks listed here have very different and specific service choices.

## AUTODIN II

The service choices are in two parts: Traffic Acceptance Categories, and Application Type. The Traffic Acceptance Categories can be mapped into and out of the IP TOS precedence reasonably directly. The Application types can be mapped into the remaining IP TOS fields as follows.

TA	DELAY	THROUGHPUT	RELIABILITY
---	----	-----	-----
I/A	1	0	0
Q/R	0	0	0
B1	0	1	0
B2	0	1	1

DTR	TA
---	---
000	Q/R
001	Q/R
010	B1
011	B2
100	I/A
101	I/A
110	I/A
111	error

## ARPANET

The service choices are in quite limited. There is one priority bit that can be mapped to the high order bit of the IP TOS precedence. The other choices are to use the regular ("Type 0") messages vs. the uncontrolled ("Type 3") messages, or to use single packet vs. multipacket messages. The mapping of ARPANET parameters into IP TOS parameters can be as follows.

Type	Size	DELAY	THROUGHPUT	RELIABILITY
----	----	-----	-----	-----
0	S	1	0	0
0	M	0	0	0
3	S	1	0	0
3	M	not allowed		

DTR	Type	Size
---	----	----
000	0	M
001	0	M
010	0	M
011	0	M
100	3	S
101	0	S
110	3	S
111	error	

## PRNET

There is no priority indication. The two choices are to use the station routing vs. point-to-point routing, or to require acknowledgments vs. having no acknowledgments. The mapping of PRNET parameters into IP TOS parameters can be as follows.

Routing	Acks	DELAY	THROUGHPUT	RELIABILITY
-----	----	-----	-----	-----
ptp	no	1	0	0
ptp	yes	1	0	1
station	no	0	0	0
station	yes	0	0	1

DTR	Routing	Acks
---	-----	----
000	station	no
001	station	yes
010	station	no
011	station	yes
100	ptp	no
101	ptp	yes
110	ptp	no
111	ptp	yes

## SATNET

There is no priority indication. The four choices are to use the block vs. stream type, to select one of four delay categories, to select one of two holding time strategies, or to request one of three reliability levels. The mapping of SATNET parameters into IP TOS parameters can thus quite complex there being  $2*4*2*3=48$  distinct possibilities.

## References

-----

- [1] Postel, J. (ed.), "Internet Protocol - DARPA Internet Program Protocol Specification," RFC 791, USC/Information Sciences Institute, September 1981.

